



ASPHALTCO

Cold asphalt

DESCRIPTION

ASPHALTCO is a bituminous emulsion in aqueous dispersion (thick paste), with the addition of mineral fillers and thickeners. The dried film is completely waterproof.

APPLICATIONS

ASPHALTCO is generally used for waterproofing and protection in the building and industrial sectors.

INSTRUCTIONS FOR USE

ASPHALTCO can be applied by brush, roller or spatula. It can be sprayed after being diluted. Apply ASPHALTCO to clean, dry surfaces. The first layer of ASPHALTCO can be diluted with clean water with a percentage of 40%. When the first coat is dry, a second coat can be applied without being diluted. Consumption depends on the type of surface and can vary from 0.5 to 1.5 kg per m². Applying a reinforcing layer between the ASPHALTCO layers improves its mechanical resistance. After drying, it is necessary to protect the ASPHALTCO film with coloured protective products (MATCOLOR) or aluminium (MAT ALU).

WARNING

Avoid applying ASPHALTCO on wet surfaces, at temperatures lower than 5°C when rain or fog is forecast. Optimal conditions should be guaranteed for at least 24 hours after application. Protect the package from frost.

Features	Values	Tolerance
Colour	Brown	
Colour of dried film	Black	
Type of product	Bituminous emulsion with fillers and thickening agents ready for use	
Viscosity	Highly viscous	
Density	kg 1,300	dm
Dry residue	700 gr/l	±3%
Specific weight	1426 gr/l	±3%
Flammability	Non-flammable	
Dilution	Clean water	
Storage	Stored in original packaging, 18 months from production date	

Matco reserves the right to alter the ratings without notice.